

K200C SERIES CAPPER

Rotary capper that
is ideal for capping
bottles with sport
caps and flat caps





FEATURES

- Small footprint
- Motorised capping allowing optimal capping speed for each cap thread
- Magnetic capping head torque can be adjusted by sleek manual action with clear torque calibration - no tools required
- Cap grippers are flexible to handle caps with small variations in diameter
- Cap unscrambler and cap chute move up and down with capping heads allowing for simple capping height adjustment
- Machine stops automatically when cap chute is empty
- Drive mechanism is maintenance free and no chains are used
- Built-in gearbox allows large format bottles to be capped on every second capping head
- Line control on discharge conveyor stops machine when conveyor is full
- Acrylic safety guarding all round
- Drip tray all round machine base
- Ergonomic design to allow easy access to operator controls
- Machine runs on 220V single phase power supply
- Under and over voltage protection
- Electronic jacking supplied as standard on machine
- Machine Dimensions: 1180mm (L) X 1180mm (W) X 2630mm (H)

K200C SERIES CAPPER SPEEDS			
	K201C	K202C	K203C
Bottles/min	120	240	300
Bottles/hr	7200	14400	18000

FILKRAFT
PACKAGING & PROCESSING EQUIPMENT

+27 (0)21 204 8517 @ sales@filkraft.com  www.filkraft.com
 Filkraft, Unit 3, The Pearl, Zandwyk Park, Old Paarl Road, Paarl, 7646, South Africa